WILKA - VORSPRUNG DURCH QUALITÄT



**Nursery solution** 

... so that we get out in an emergency ...











Pic. with GfS door guard

Pic. with GfS e-Bar®

## **Escape doors according to EN 179 and EN 1125**

The WILKA nursery solution consisting of the nur- lock makes it possible to independently activate sery lock and proven GfS products – EH door guard for escape doors in compliance with EN 179 or e-Bar® for escape doors in compliance with e-Bar® push bar of escape doors complying with EN 1125 -secures the main entrance to the nursery. It prevents children from going outside unnoticed and so putting themselves at risk. For stallation. The upper handle is only accessible to adults, the nursery solution is operated intuitively, dispensing with sophisticated and complex elec- triggering an alarm. In an emergency, children tronics.

Thus the nursery solution lightens the load of preschool teachers and nursery nurses in their daily routine, which is not always easy. The nursery

the upper and lower handle of escape doors complying with EN 179 or the upper handle and the EN 1125. Both the EH door guard and the e-Bar® can be battery-operated and so save on costly inadults (e.g. parents or staff), who can exit without can escape on their own, whereupon the relevant emergency exit safeguards become effective.





## **WILKA**

## Kindergarten lock:

- Robust product solution without no extra annual maintenance costs. Optimally tailored to the special needs of nurseries.
- Meets the requirement of EN 179/1125 regarding the installation height of the metal mount (Appendix A 900-1100 mm).
- Escape doors in nurseries can be very easily adapted to the requirements of the relevant emergency exit standards.
- Different handle heights can be implemented (standard 1.60 m)
- Intuitive use of the upper handle for adults who want to leave the building without triggering an alarm

- Keep and accessory components of the 6000 escape door series can be combined with the nursery solution for the inactive leaf of double-leaf doors.
- Escape door functions E and B
- Available in 30 45 mm backset
- Optional latch bolt and dead bolt 3 mm or 5 mm extended
- Distance 92 mm
- Prepared for profile cylinder or for Swiss circular cylinder
- Flat or U-shaped forend available
- Controlled latch retainer optional











661K

9650

This is a factor which distinguishes this product solution from many nursery solutions where the handle is positioned so high that children are unable to vacate the building in the case of danger. The applicable escape door

standards EN 179 and EN 1125 clearly suggest even reducing the usual handle height of 1050 mm if it is predominantly children who are in the building.

The nursery solution solves this problem in an ideal way and keeps the necessary expenditure to an acceptable level, avoiding follow-up costs that might be incurred with other alternative locking systems. It is, in fact, a product solution that is tailored to the needs and requirements of nurseries and day care centres and does not exclude children from the important issue of personal protection.





WILKA Schließtechnik GmbH
Postfach 10 05 70 · 42505 Velbert
Fon: +49 (0) 20 51 / 20 81-0 · Fax: +49 (0) 20 51 / 20 81-151
info@wilka.de · www.wilka.de